

JU10800V-17500 Wide Platen

JUPITER 5 Series: Two-Platen
Servo-Hydraulic



Clamping Unit		JU10800 V Wide Platen
Clamping Force	kN	10800
	US Tons	1214
Mold Opening Stroke (Min/Max)	mm	1950/1350
	in.	76.77/53.15
Minimum Mold Height	mm	600
	in.	23.62
Maximum Mold Height	mm	1200
	in.	47.24
Maximum Daylight	mm	2550
	in.	100.39
Distance Between Tie-Bars (HXV)	mm	1445x1195
	in.	56.89x47.05
Platen Dimensions (HXV)	mm	2000x1770
	in.	78.74x69.69
Ejector Stroke	mm	350
	in.	13.78
Ejector Force	kN	230
	US Tons	26
Maximum Mold Weight*	t	23
	lbs.	50706



Specification



JU10800V-17500 Wide Platen

JUPITER 5 Series: Two-Platen
Servo-Hydraulic

Injection Unit		17500		
Screw & Barrel Designation		A	B	C
Screw Diameter	mm	130	140	150
	in.	5.12	5.51	5.91
Screw L/D Ratio	L/D	24	22.3	20.8
Injection Volume (theoretical)	cm ³	8362	9698	11133
	cu.in.	510.28	591.81	679.38
Injection Weight (PS)	g	7609	8825	10131
	oz.	268.40	311.29	357.36
Injection Rate (PS)	g/s	1281	1486	1705
	oz./s	45.19	52.42	60.14
Injection Pressure	MPa	185	160	139
	psi	26832	23206	20160
Injection Pressure (max)*	MPa	210	181	158
	psi	30458	26252	22916
Plasticizing Rate (GPPS)	g/s	168	192	220
	oz./s	5.93	6.77	7.76
Plasticizing Rate (HDPE)	g/s	252	283	336
	oz./s	8.89	9.98	11.85
Screw Speed	rpm	102	102	102



Absolute Haitian Corporation • 33 Southgate St. Worcester, MA 01610
508-459-5372 • absolutehaitian.com

Specifications subject to change without notice



Rev 2 8/15/2024


JU10800V-17500 Wide Platen

JUPITER 5 Series: Two-Platen
Servo-Hydraulic


Other		
Pump Motor Power	kW	195
Heater Power	kW	123
Machine Dimension (LxWxH)	m	11.25x3.45x4.34
	in.	443x136x171
Machine Weight	t	60
	lbs.	132277
Hopper Capacity	kg	50
	lbs.	110
Oil Tank	l	1670
	gal	441

***NOTE:**

1. Injection Pressure (max) uses the machine's regeneration oil circuit to increase the injection pressure. This function will reduce injection control and repeatability. The standard "Injection Pressure" specification is the maximum injection pressure in a normal operating mode.
2. Moving platen max mold weight is 2/3 of total max mold weight.
3. Electric screw drive (screw rotate) is standard for injection units under 11500. For injection units 11500 and above electric screw drive is optional.
4. Machine dimensions and weights are based on the international standard configuration and are for reference only. Any options or country specific requirements will affect this. Contact Absolute Haitian service department for machine specific information.
5. Power requirements are based on the international standard configuration and are for reference only. Any options or country specific requirements will affect this. Contact Absolute Haitian service department for machine specific information.



Fixed Platen



Moving Platen



Absolute Haitian Corporation
33 Southgate St. Worcester, MA
T: +1 508-792-4305
www.absolutehaitian.com

Title: JU V 10800W Fixed & Moving Platens Drawing				
Machine Model: JU V 10800W			Sheet: 1 of 1	
Machine Serial Number:			Drawn By: Harry	Date: 6/25/2024
Machine Tonnage:			Chkd By: LEON XIE	Date: 6/25/2024
Revision	Date:	Drawing #:	NOT TO SCALE	Size: 11 X 17 "B"
Rev #: 1				Units: mm / [in]
Rev #: 2				Material:
Rev #: 3				Part:
Rev #: 4				Part:
Rev #: 5				Part:

PLEASE READ:

The designs on this drawing were validated using machine manufacturer's drawings and/or information supplied by Absolute or the customer. It is the responsibility of the customer to review and confirm that all dimensions are consistent with the application intended and in accordance with the facility requirements for space, part clearance, overhead clearance, or any other interference. By signing this document, the customer accepts full responsibility for this design and application.

Customer:

Customer Approval:

Authorized Signature

Notes: